

The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.



Description	EN388 : 2016						Suitable use:						
							General Building	Trade	Automotive	Engineering	Waterproof		Scaffolding
<b>Latex Foam Hi-Vis Yellow</b>	2	1	2	1	X		✓	✓				✓	
<b>Max Dexterity Nitrile</b>	3	1	2	1	X			✓	✓	✓			
<b>Nitrile Coated Red Knitted</b>	4	1	2	1	X			✓	✓	✓		✓	
<b>Nitrile Inspection</b>	4	1	2	1	X			✓	✓	✓		✓	
<b>Premium Latex Examination</b>	-	-	-	-	X			✓	✓	✓	✓		
<b>Premium Nitrile Examination</b>	-	-	-	-	X			✓	✓	✓	✓		
<b>PVC Gauntlet 27cm 11in</b>	4	1	2	1	X			✓	✓		✓		
<b>PVC Gauntlet 45cm 18in</b>	4	1	2	1	X			✓	✓		✓		
<b>Red PVC Knitwrist Cotton</b>	3	1	2	1	X						✓		
<b>Vibration Resistant Latex Foam</b>	1	1	2	X	X		✓		✓	✓		✓	
<b>Waterproof with Latex Palm</b>	2	1	3	1	X			✓	✓	✓	✓		
<b>Welders Gauntlet 14in</b>	4	1	4	3	X				✓	✓			
<b>White PU Coated</b>	3	1	2	1	X		✓	✓					
<b>Work Gloves with Touchscreen</b>	2	1	3	1	X			✓	✓	✓			
<b>13in Nitrile Gauntlets with Flock Lining</b>	3	1	0	1	X				✓		✓		